

54, Islampura Street, 5-A, Ghaswala Bldg., 1st Floor, Nr. Madhav Baug, Girgaon, Mumbai - 400 004. (India)

INSTRUMENTS (INDIA)

OUR MOTO: QUALITY INSTRUMENTS & CUSTOMER SATISFACTION OUR EXPERIENCE: SERVING TO INDUSTIRES SINCE 1978

# **GLASS TUBE LEVEL INDICATOR (MOVING BOLT TYPE)**



#### MODEL NO. GTMB-LI-S

Small size level indicator for normally small oil tanks level indication.

Connections posible 1/4" BSP (M) to 1" BSP (M). Bottom side only.

Top side cap with vent hole.

Pipe length 1" to 24".

Material of construction M.S., Brass, 304 S.S., 316 S.S., or other as required.

Glass tube: Borosilicate, having 12mm or 16mm or 19mm O.D. as per connection size

Glass tube protective casing: normally M.S., Ch. plated having slitted front & back for viewing

Temperature rating upto 150°C. Pressure upto 15 PSIG

#### MODEL NO. GTMB - LI -2S

Small size level indicator for normally small oil tanks level indication.

Connections posible 1/4" BSP (M) to 1" BSP (M)., on both side

Pipe length 1" to 12".

Material of construction M.S., Brass, 304 S.S., 316 S.S., other as required.

Glass tube: Borosilicate, having 12mm or 16mm or 19mm O.D. as per connection size

Glass tube protective casing: normally M.S., Ch. plated having slitted front & back for viewing

Temperature rating upto 150°C. Pressure rating upto 15 PSIG



# **ACRYLIC BODY LEVEL INDICATOR (MOVING BOLT TYPE)**



## MODEL NO.AB MB - LI -2S

Small size level indicator for normally small oil tanks level indication.

Connections possible M10, M12, Male threadings at both side

Standard connection C.C.: 3"/4"/5"

Material of construction main chamber acrylic plastic, Bolt M.S. Powder coted

Acrylic chamber protective casing: M.S., powder coated,

Temperature rating upto 50°C. Pressure rating upto 7 PSIG

### MODEL NO. GTMB - LI -2S

Small size level indicator for normally small oil tanks level indication.

Connections posible 1/4" BSP (M) to 1" BSP (M)., on both side

Pipe length 1" to 12".

Material of construction M.S., Brass, 304 S.S., 316 S.S., other as required.

Glass tube: Borosilicate, having 12mm or 16mm or 19mm O.D. as per connection size

Glass tube protective casing: normally M.S., Ch. plated having slitted front & back for viewing

Temperature rating upto 150°C. Pressure rating upto 15 PSIG



Phone: 91-22-2388 4279 / 2385 3044 / 2387 6566 • Fax: 91-22-2387 6566 / 2385 3044 • Email: teleinst@vsnl.com / teleinst@gmail.com

Website: www.telelinindia.com